



Case Study

Small Macro cell Sync Solution

Speakers

Mr. Sherif Abdel Hamid, Senior Engineer, Orange Egypt

Dr. Djamila Duc, Business Development Director MEA, Oscilloquartz

Orange – Egypt (i.e. Mobinil)

- Ist and biggest Mobile Operator in Egypt
- > 2G/3G/4G/LTE mobile operator
- > Entity of Orange Group since 2012 \rightarrow 100% shares



Ŵ

 $\ensuremath{\mathbb{C}}$ 2014 ADVA Optical Networking. All rights reserved. Confidential.

OSA & ORANGE : Long-Term Relationship !

- > OSA & Orange met in 1997 thanks to NEC
- > OSA Products deployed in Orange Network:
 - Cesium
 - > SSU : OSA 5548C with PTP cards
 - > GNSS receivers : OSA 5240, OSA 5210
 - PTP Grand Masters : OSA 5421 (recently)
 - Probing solution
 - Network Management systems: Sync View+ and FSP NM
- Network Design Services and Others



 $\ensuremath{\mathbb{C}}$ 2014 ADVA Optical Networking. All rights reserved. Confidential.

Heading towards Carrier Ethernet Networks!

- Rapid deployment of Small-cells solutions that is compatible only with IP Backhauling
- Existing plan to Shift all existing RAN to IP with accordance to IP-2020 Program.
- In accordance with the above plan, Transport Network deployments moves from legacy SDH, PDH towards IP-MPLS Network deployment

4

 Existing TDM synchronisation using legacy PRC/SSU architecture was not suitable any more!



© 2014 ADVA Optical Networking. All rights reserved. Confidential.


Network Restrictions & explored solutions

- Backhauling capability to handle such Small cell deployment is only through 3rd party HDSL (i.e. Telecom Egypt).
- Part of IP-MPLS cloud is also 3rd Party with unknown PDV performance
- Network is PTP UNaware Network (brown field Network)

Which Solution for best sync performances : SyncE vs PTP ?


- SyncE → Not suitable for such Small Cell deployment over HDSL, can only be used for Macro Site Deployment
- PTP 1588-V2 → Suitable for Small Cell deployment but with Unknown Performance over PTP unaware Network/3rd Party leased lines







Test 1: Macro Node-B Through MW link chain with ITUT **G.82651** (Frequency Synchronization)



Conclusion

- Successful testing and best approach determined & approved
- Adopted product is OSA 5421
 - PTP Delivery (Freq. & phase with 512 slaves capacity) with latest ITU-T standards
 - > 16X **BITS** outputs
 - Probing or real-time monitoring included
 - > **NTP** server capabilities
- Solution currently under deployment (phases-based)
- Ongoing 4G design & OSA 5421 may be massively deployed in future ISA







Thank you for your attention Any Questions?

info@advaoptical.com




IMPORTANT NOTICE

The content of this presentation is strictly confidential. ADVA Optical Networking is the exclusive owner or licensee of the content, material, and information in this presentation. Any reproduction, publication or reprint, in whole or in part, is strictly prohibited.

The information in this presentation may not be accurate, complete or up to date, and is provided without warranties or representations of any kind, either express or implied. ADVA Optical Networking shall not be responsible for and disclaims any liability for any loss or damages, including without limitation, direct, indirect, incidental, consequential and special damages, alleged to have been caused by or in connection with using and/or relying on the information contained in this presentation.

PTP 1588 -V2 Tests & results (2)



PTP 1588 -V2 Tests & results (3)

