



# International Timing & Sync Forum 2022

#ITSF2022



# PTP+Squared - an Overlay Network

Ian Gough

*Co-Founder Timebeat.app*

#ITSF2022




# IEEE1588/PTP is a Great Achievement!\*

- The success of getting PTP support built-in to most commodity hardware network controllers MACs and PHYs is quite an achievement
- The architects of IEEE1588-2008 have achieved some important milestones
  - For example; dishonest practices in broker-dealers has been significantly curtailed by MiFID regulations - in no small part because sequencing is now a recorded fact. A leads to B leads to C.
  - Their work allows for great accuracy and the impact that this has had is tangible in many sectors
- The way PTP works is brilliant
  - PTP solves real problems in the real world

\*However.... There are a few unresolved issues.... 😊

...Let's talk about them...

# Boundary clock distribution is literally nothing but single points of failure and unquantifiable error




Everything **green** is a single-point-of-failure. Every :

- Clock
- Switch
- Host
- PTP Session / Connection between them!

The single-parent principle is everywhere

# Boundary clock distribution and BMC

- Here is a typical PTP deployment
- It is unknown if nodes have the same time
- In the real world, when we measure “no, they don’t”
- The best master clock concept of self announcing how good the quality of the time distributed is “not a good strategy”™
- It’s hard not to think that BMC was an afterthought in PTP
  - It’s also optional
- Problems changed when we went from ms->us->ns->ps
  - What used to be ignorable and insignificant is now the opposite




We thought about how to solve these problems...

... Introducing PTP+Squared...




# Suppose we turn the tree upside down....

- Now any server has multiple paths to sources of time
- All of the paths can be compared in real time
- Error of variation can be communicated downstream in a cumulative fashion
- In that way if any part of the tree becomes congested it will be visible and time can be taken from a better path



# How do we create the reverse tree / mesh structure?

- How is it done? & What does it look like?
- We used a peer-2-peer distributed hash table to create an overlay network to PTP.
- The overlay network sets up unicast sessions between PTP participants in the grid
  - we call them “grid nodes” and “root nodes”
- Everything is completely dynamic and in real time
  - We used D3.js to visualize it, it’s cool 😊





# Error is quantifiable and we compare paths

- Squared nodes showing their cumulative error (from source to server).
- Above certain thresholds the bubbles grow and turn orange and red.
- This is 8x faster than real-time, so 5 1/2 minutes condensed into 40 seconds.
- Here the mesh goes from largely bad to largely good in that time.



# Two types of peer discovery mechanisms



The two approaches are not mutually exclusive, and nodes can use one or both in the same PTP+Squared network, but pure DHT is nearly always the better approach.

Paths created dynamically using either:  
mDNS (rfc6762)

- Quick and easy: zero config
- Not particularly scalable

DHT

- Requires a few nodes whose IP and public key are known
- Highly scalable

# What is the attraction

## Benefits

- This model can support millions of nodes in terms of scale and still have remarkably good accuracy
- The scaling model becomes vertical instead of horizontal.
  - Scale is achieved through many nodes that each do negligible work
  - Even with 3 hops between time source and final node (a cumulative error of +/-15ns can be achieved) this can easily support tens of thousands of nodes
- Time is compared from different nodes at all levels of the network. Verification of the time received is completely built into the backbone of the system (very much unlike BMCA)
- Everything uses signed / verified / authenticated public-private key X.509 type stuff and is ultra secure
- I.e. when the system speaks with a node or receives a message, it is certain™ of the sender
- PTP+Squared takes IEEE1588 PTP systems from a “blind faith” model into a verified “trust based” model.

THANK YOU

